/ SPIRAL AL GP

Structure
Spiral PVC hose with rigid shock-resistant PVC reinforcement.

Applications
Discharge and suction of tank cars or for uses at low temperatures. Industrial duty, agricultural use and for the passage of food liquids. Heavy duty.

Material
Suitable for passage of food liquids in compliance with EU 10/2011 for simulants A, B and C. Phthalate free.

Note
High flexibility.

Struttura
Tubo spiralato in PVC con spirale in PVC rigido antiurto.

Applicazioni
Per spurghi e per aspirazione di carri botte e per usi alle basse temperature. Per impieghi medi nel settore industriale, agricolo e per il passaggio dei liquidi alimentari. Impieghi gravosi.

Materiali
Conforme alle direttive EU 10/20111 per il passaggio di liquidi alimentari per simulanti A, B e C. Esente da ftalati.

Note
Alta flessibilità.



SINGLE SPIRAL / *SPIRALE SINGOLA*

Plasticised PVC / *PVC plastificato*

Rigid PVC spiral / *Spirale in PVC rigido*

Items available on stock
Articolo disponibile a magazzino

Code *Codice*	Ø internal (mm) *Ø interno (mm)*	Weight (gr) *Peso (gr)*	Lenght (m) *Lunghezza (m)*	W.P. Bar	B.P. Bar	Radius	Vacuum (mH²0)	EAN Code *Codice EAN*	m/plt	€/m
481261	25	500	50	8	24	140	9	802148 481261 5		
481262	30	570	50	7	21	165	9	802148 481262 2		
481263	35	650	50	6	18	192	9	802148 481263 9		
481264	40	720	50	6	18	220	9	802148 481264 6		
481265	50	1050	50	8	24	280	9	802148 481265 3	150	
481266	60	1250	50	7	21	330	9	802148 481266 0		
481126	76	1700	30	6	18	400	9	802148 481126 7		
481267	80	1850	30	6	18	440	9	802148 481267 7	90	
481268	90	2250	30	6	18	500	9	802148 481268 4		
481269	100	2700	30	6	18	550	9	802148 481269 1	90	
481270	120	3600	30	5	15	660	9	802148 481270 7		
481271	150	5000	20	4	12	840	9	802148 481271 4		
481272	160	5600	20	4	12	880	9	802148 481272 1		
481273	200	10000	10	0,5	1,5	1400	9	802148 481273 8		